



## PROFILATI a T a spigoli vivi e tondi

dimensioni profilo base mm	altezza mm	spessore mm	peso kg/m	dimensioni profilo base mm	altezza mm	spessore mm	peso kg/m
20	20	4,0	1,13	80	80	10	11,80
25	25	4,5	1,61	100	100	11	16,40
30	30	5,0	2,16	120	120	13	23,20
35	35	5,5	2,78	140	140	15	31,30
40	40	6,0	3,49				
45	45	6,5	4,26				
50	50	7	5,11				
60	60	8	7,03				
70	70	9	9,26				

## PROFILATI a T a spigoli vivi e tondi



dimensioni profilo base mm	altezza mm	spessore mm	peso kg/m
20	20	3	0,88
25	25	3,5	1,29
30	30	4	1,75
35	35	4,5	2,31
40	40	5	2,95
45	45	5,5	3,67
50	50	6	4,43
60	60	7	6,23
70	70	8	8,32
80	80	9	10,70



## TRIANGOLI RETTANGOLI LAMINATI A CALDO DI PRECISIONE

lato	7x7	10x10	15x15	20x20	25x25	30x30
kg/ml	0,22	0,45	0,92	1,60	2,50	3,70



## PROFILATI AD U SERIE NORMALE

h	b	a	e	r	sezione	peso	momenti di inerzia		moduli di resistenza		raggi di inerzia	
							Jx	Jy	Wx	Wy	Ix	Iy
mm	mm	mm	mm	mm	cm <sup>2</sup>	kg/m	cm <sup>4</sup>	cm <sup>4</sup>	cm <sup>3</sup>	cm <sup>3</sup>	cm	cm
30	33	5	7	7	5,44	4,27	6,39	5,33	4,26	2,68	1,08	0,99
40	35	5	7	7	6,21	4,87	14,10	6,68	7,05	3,08	1,50	1,04
50	38	5	7	7	7,12	5,59	26,40	9,12	10,60	3,75	1,92	1,13
65	42	5,5	7,5	7,5	9,03	7,09	57,50	14,10	17,70	5,07	2,52	1,25
80	45	6	8	8	11,0	8,65	106	19,4	26,5	6,35	3,10	1,33
100	50	6	8,5	8,5	13,5	10,6	205	29,1	41,1	8,45	3,91	1,47
120	55	7	9	9	17,0	13,3	364	43,1	60,7	11,1	4,63	1,59
140	60	7	10	10	20,4	16,0	605	62,5	86,4	14,7	5,45	1,75
160	65	7,5	10,5	10,5	24,0	18,9	925	85,1	116	18,2	6,21	1,88
180	70	8	11	11	28,0	22,0	1354	114	150	22,4	6,96	2,01
200	75	8,5	11,5	11,5	32,2	25,3	1911	148	191	26,9	7,71	2,14
220	80	9	12,5	12,5	37,4	29,4	2691	196	245	33,5	8,48	2,29
240	85	9,5	13	13	42,3	33,2	3599	247	300	39,5	9,22	2,42
260	90	10	14	14	48,3	37,9	4824	317	371	47,8	10,0	2,56
280	95	10	15	15	53,4	41,9	6276	398	448	57,2	10,8	2,73
300	100	10	16	16	58,8	46,1	8028	493	535	67,6	11,7	2,90
320	100	14	17,5	17,5	75,8	59,5	10870	597	679	80,6	12,10	2,81
350	100	14	16,0	16	77,3	60,6	12840	570	734	75,0	12,90	2,72
380	102	13,5	16,0	16	80,4	63,1	15760	615	829	78,7	14,00	2,77
400	110	14	16,0	16	91,5	71,8	20350	846	1020	102	14,90	3,04

## PROFILATI AD U SERIE SPECIALE



H mm	B mm	S mm	Kg/mt
25	12	4	1,30
30	15	4	1,74
30	15	5	2,20
35	17	4	2,15
40	20	5	2,87
50	25	5	3,86
60	30	6	5,07